

REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	YCH 03/07/07'		


NOTES:

- ELECTRICAL CHARACTERISTICS:
 - CONTACT RESISTANCE: 50mΩ Max.
 - DIELECTRIC WITHSTANDING VOLTAGE: 500V AC(rms) FOR 1 MINUTE.
 - INSULATION RESISTANCE: 1000MΩ Min.
- ENVIRONMENT CHARACTERISTICS:
 - OPERATING TEMPERATURE: 0°C~+85°C.
 - STORAGE TEMPERATURE: -20°C~+70°C.
 - CONTACT RETENTION FORCE: 1kgf Min.
 - CONTACT WITHDRAWAL FORCE: 38g min
- PRODUCT NUMBER CODE:

DS1023-04- X X X X X X

 - CONNECTOR Q'TY
 - MOUNTING TYPE
V: V/T TYPE
 - HOUSING COLOR
B: BLACK
 - CONTACT PLATING
0: SELETIVE GOLD FLASH
8: FULL GOLD FLASH
 - CONNECTOR TYPE
2: 2 in 1
 - No. OF CONTACTS
2*3
 - SERIES No.
DS1023-04

Tel: 86-574-63508787
Fax: 86-574-63510817

GENERAL TOLERANCE	ANGLE TOLERANCE	PROJECTION	⊕	TITLE	Female Header with Pin Header
X. ±0.60	X. ±5°	UNITS	mm	pitch 2.54mm V/T Stack TYPE	
.X ±0.38	.X ±3°	SHEET SIZE	A4	SERIES	DS1023-04 SERIES
.XX ±0.25	.XX ±2°	 宁波正青电子有限公司 NINGBO ZHENQIN ELECTRONIC CO. LTD			
DRAWING TYPE	CUSTOMER				
SCALE	1:1 SHEET 1 OF 1				
DRAWING NO.	C-DS1023-04-XXXXXX				